

Please add the following claims 14-26:

14. A framing system for adjustably connecting building components comprising:

5       an outer stud,  
          an interior support member, and  
          a connecting clip wherein

      said outer stud includes a web from which two flanges extend perpendicularly,

10       said web having at least a first elevation and a second elevation,

          said second elevation of said web located between said flanges,

          each of said flanges having receptors for engaging said  
15   interior support member,

          said outer stud having a terminal end;

          said interior support member having an inner surface that is substantially perpendicular to said flanges and that is substantially flush with said second elevation of said web,

20       an attachment device for securing said inner surface and said second elevation together,

          said inner surface having bracing arms extending therefrom toward said flanges,

said bracing arms having extensions for engaging said  
receptors with the interior support member; and,

said connecting clip having a top and sides,

said connecting clip frictionally engaging said terminal  
5 end of said outer stud,

said top having a tab extending therefrom between said  
flanges and that is substantially flush with said second  
elevation of said web,

an attachment device for securing said tab and said second  
10 elevation together.

15. The framing system of claim 14 wherein the outer stud  
has holes in the receptors for attachment devices for securing  
the inner surface of the interior support member to the outer  
15 stud.

16. The framing system of claim 14 wherein the flanges of  
the outer stud have a peripheral end, which have holes for  
attachment devices for securing the outer stud to another  
20 structure.

17. The framing system of claim 14 wherein the inner  
surface of the interior support member has a third elevation and

a fourth elevation, and said fourth elevation of said inner surface located between said bracing arms.

18. A framing system comprising:

5 an outer stud and an interior support member wherein said outer stud includes a web from which two flanges extend perpendicularly,

said web having at least a first elevation and a second elevation,

10 said second elevation of said web located between said flanges,

each of said flanges having receptors engaging said interior support member,

said interior support member having an inner surface that  
15 is substantially flush with said second elevation of said web,

said inner surface having bracing arms extending therefrom toward said flanges, and

said bracing arms including a portion for engaging said receptors of said flanges whereby said framing member may be  
20 installed in a wall to provide additional support.

19. The framing system of claim 18 wherein the outer stud has holes in the receptors for attachment devices for securing

the inner surface of the interior support member to the outer stud.

20. The framing system of claim 18 wherein the flanges of  
5 the outer stud have a peripheral end, which have holes for attachment devices for securing the outer stud to another structure.

21. The framing system of claim 18 wherein the inner  
10 surface of the interior support member has a third elevation and a fourth elevation, and

said fourth elevation of said inner surface located between said bracing arms.

15 22. The framing system of claim 19 wherein said fourth elevation of said inner surface has a hole for the attachment device to secure said inner surface and the second elevation together.

20 23. The framing system for adjustably connecting building components of claim 19 wherein said bracing arms have extensions which have a hole for said attachment device to further secure said internal support member and said outer stud together.

24. The framing system for adjustably connecting building components of claim 18 wherein a connecting clip is secured to a terminal end of said framing system.

5        25. A framing system comprising:  
an outer stud and an interior support member wherein  
said outer stud includes a first web from which two flanges  
extend perpendicularly,  
said first web having at least a first elevation and a  
10 second elevation,  
said second elevation of said first web located between  
said flanges,  
each of said flanges having receptors engaging said  
interior support member,  
15 said interior support member having a second web that is  
substantially flush with said second elevation,  
said interior support member having bracing arms extending  
from said second web of the interior support member toward said  
flanges; and  
20 said bracing arms including a portion for engaging said  
receptors of said flanges whereby said framing member may be  
installed in a wall to provide additional support.